



Murotti Angelo srl

Version no. 3

Revision date 24/07/2015

ASCOR AD

Printed on 24/07/2015

Page no. 1/13

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and the company/undertaking

1.1. Product identification

Name ASCOR AD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description/Use RINSE POLISH

1.3. Details of the supplier of the safety data sheet

Company name Murotti Angelo srl
Address Via Caduti di Sabbiuno, 69
City and Country 40053 Loc. Bazzano- VALSAMOGGIA (BO)
Italy
tel. 051 832255
fax 051 832956

e-mail of the competent person,
person responsible for the safety data sheet murotti.ascor@libero.it

1.4. Emergency telephone number

For urgent information contact Poison Center: 02/66101029- Company headquarters: tel 051/832255

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions of Regulation (EC) 1272/2008 (CLP) (and amendments). Therefore the product requires a safety data sheet according to the provisions of Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Classification and hazard statements:

Eye irritant, category 2	H319	Causes serious eye irritation.
Skin irritant, category 2	H315	Causes skin irritation.

2.2. Labeling elements.

Danger identification pursuant to Regulation (EC) 1272/2008 (CLP) and subsequent amendments.



Warnings: Warning

**ASCOR AD**

Hazard statements:

H319 Causes serious eye irritation.
H315 Causes skin irritation.

Precautionary statements:

P264 Wash thoroughly with water after handling.
P280 Wear protective gloves/eye protection/face protection.
P302+P352 IF ON SKIN: wash with plenty of water / . . .
P332+P313 If skin irritation occurs: get medical advice.

2.3. Other hazards.

According to the available data, the product does not contain PBT or vPvB substances in a percentage higher than 0.1%.

SECTION 3. Ingredients/composition information.**3.1. Substances.**

Information non applicable.

3.2. Mixtures.

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
ALKOXYLATED LONG CHAIN ALCOHOL		
CAS. 166736-08-9	5 - 10	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC. -		
INDEX. -		
Nr. Reg. 02-2119630747-33-0000		
ALKOXYLATED FATTY ALCOHOL, POLYMER		
CAS. 166736-08-9	5 - 10	Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC. -		
INDEX. -		
Nr. Reg. 02-2119630747-33-0000		
2-PROPANOL		
CAS. 67-63-0	0 - 5	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC. 200-661-7		
INDEX. 603-117-00-0		
Nr. Reg. 01-2119457558-25		

Note: Upper range value excluded.

The full text of the hazard statements (H) is given in section 16 of the sheet.



SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if worn. Immediately flush eyes with plenty of water for at least 15 minutes while keeping eyelids raised. Get medical advice if the problem persists.

SKIN: Remove any contaminated clothing. Wash immediately with plenty of water. If the irritation persists, get medical advice. Wash any contaminated clothing prior to using again.

INHALATION: Take the person outside. If they have difficulty breathing, seek medical advice immediately.

INGESTION: Seek medical advice immediately. Induce vomiting only if directed to do so by the doctor. Never give anything by mouth to an unconscious person or unless authorized by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures

5.1. Extinguishing media.

APPROPRIATE EXTINGUISHING MEDIA

Use extinction equipment: carbon dioxide, foam, chemical powder. For product losses and leakages that have not set on fire, water spray can be used to disperse the flammable vapors and protect those working to stop the leakage.

INAPPROPRIATE EXTINGUISHING MEDIA

Do not use water spray. Water is not effective in extinguishing the fire, but can be used to cool closed containers exposed to the flames, preventing explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may build up in containers exposed to fire and which may explode. Avoid inhaling any combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Cool the containers with jets of water to prevent product decomposition and the development of substances that are potentially hazardous for the health. Always wear full fire protection equipment. Collect all water used to extinguish the fire; this must not be drained into the mains sewer. Dispose of contaminated water used to extinguish the fire and other fire residues in compliance with the laws in force.

EQUIPMENT

Normal firefighting clothing, such as self-contained, open-circuit compressed air breathing apparatus (EN 137), flameproof suit (EN469), flameproof gloves (EN 659) and Fire Brigade boots (HO A29 or A30).



SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear appropriate protection devices (including personal protective equipment as listed in section 8 of the safety data sheet) to prevent contamination of skin, eyes and personal clothing. These indications are valid for both workers during handling and emergency interventions.

6.2. Environmental precautions

Do not allow the product to penetrate into sewers, surface and ground waters.

6.3. Methods and material for containment and cleaning up

Aspirate the leaked product into appropriate containers. Assess the compatibility of the container to use with the product, checking section 10. Absorb the remaining product with inert absorbent materials.

Make sure that the leakage site is well aired. Check any incompatibility of the materials with the containers in section 7. Contaminated material must be disposed of in compliance with the provisions laid down in point 13.

6.4. Reference to other sections

Any information concerning personal protection and disposal are given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safety handling

Keep away from heat, sparks and live flames, do not smoke or use matches or lighters. Vapors may catch fire in an explosion, prevent them from building up by keeping doors and windows open and ensuring cross ventilation. Without adequate ventilation, vapors may accumulate on the ground and catch fire even after some time, with the risk of flash-back. Avoid the accumulation of electrostatic charge. Connect to an earthed socket when working with large packaging during decanting operations and wear antistatic shoes. Fast flow or agitation of the liquid in the piping and equipment may cause the formation and accumulation of electrostatic charge. To prevent fire and explosion hazards, never use compressed air for handling. Open the containers carefully, they may be pressurized. Do not eat, drink or smoke during use. Avoid release to the environment.

WARNING: do not store in containers other than the original one; risk of fatal errors if exchanged for drinks.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the closed containers in a well-ventilated place away from direct sunlight. Store in a cool, well-ventilated place away from heat sources, live flames, sparks or other sources of ignition. Keep the containers away from any incompatible materials, check section 10.

7.3. Specific end use(s)

Information not available.

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Reference Regulations:

TLV-ACGIH

ACGIH 2014

2-PROPANOL**Threshold Limit Value**

Type	State	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		492	200	983	400

Predicted no effect concentration in the environment - PNEC.

Reference value for sediment in fresh water

552

mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of Exposure	Effects on consumers.			Effects on workers			Systemic acute	Local chronic	Systemic chronic
	Local acute	Systemic acute	Local chronic	Local acute	Systemic acute	Local chronic			
Inhalation.								VND	500 mg/m3

Key:

(C) = CEILING ; INHALAB = Inhalable Fraction ; RESPIR = Respirable Fraction ; TORAC = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NHI = no hazard identified.

8.2. Exposure controls

Considering that the use of appropriate technical measures should always take priority over personal protective equipment, ensure that the working environment is well ventilated using a local aspiration system. Personal protective equipment must carry the CE marking to certify conformity to the regulations in force.

Provide emergency eye wash and shower facilities.

HAND PROTECTION

Protect the hands with category III work gloves (ref. EN 374).

In choosing appropriate work glove material consider: compatibility, degradation, breakage time and permeation.

Work glove resistance to chemical agents for preparations must be checked before use, as it could be unpredictable. Glove wear depends on the duration and methods of use.

SKIN PROTECTION

Wear category II professional work clothes with long sleeves and safety footwear (ref. Directive 89/686/EEC and standard EN ISO 20344). Wash with soap and water after removing protective clothing.

EYE PROTECTION

It is recommended to wear protective airtight goggles (ref. standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) of the substance or one or more of the substances in the product is exceeded, wear a mask with an A type filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use. (ref. EN 14387). In the presence of gas or other types of vapors and/or gas or vapors with particles (aerosol, fumes, mist, etc.) use combined filters.

Respiratory protection must be used if the technical measures adopted are not sufficient to limit the exposure of the workers to the considered threshold values. The protection provided by masks is in any case limited.



If the substance in question is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear self-contained, open-circuit compressed air breathing apparatus (ref. EN 137) or fresh air hose breathing apparatus (ref. EN 138). Refer to standard EN 529 to choose the appropriate respiratory protection.

ENVIRONMENTAL EXPOSURE CONTROLS

Production process emissions, including those from ventilation equipment, must be checked in order to comply with environmental protection regulations.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Pale blue
Odor	Characteristic
Olfactory threshold.	Not available.
pH.	5
Melting or freezing point	Not available.
Initial boiling point	Not available.
Boiling interval	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability of solids and gases	Not available.
Lower flammability limit	Not available.
Upper flammability limit	Not available.
Lower explosive limit	Not available.
Upper explosive limit	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.992 Kg/l
Solubility	Soluble
Partition coefficient: n-octanol/water	Not available.
Ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidizing properties	Not available.

9.2. Other information

VOC (Directive 1999/13/EC):	5.00 %	-	49.59	g/liter.
VOC (volatile carbon):	2.94 %	-	29.16	g/liter.

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.



ASCOR AD

10.3. Possibility of hazardous reactions

Vapors may form explosive mixtures with air.

10.4. Conditions to avoid

Avoid overheating. Avoid the accumulation of electrostatic charge. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapors that are potentially dangerous to the health may be released.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

If no experimental toxicological data is available for the product, any health hazards have been assessed according to the properties of the contained substances, in line with the criteria laid down in the reference regulations for the classification. Therefore consider the concentration of any single hazardous substances referred to in sect. 3, to assess the toxicological effects deriving from exposure to the product.

Acute effects: contact with eyes causes irritation; symptoms may include: reddening, oedema, pain and lacrimation. Ingestion can cause health problems, including abdominal pain, heartburn, nausea and vomiting.

Acute effects: contact with skin may cause irritations with erythema, oedema, dryness and cracking. Ingestion can cause health problems, including abdominal pain, heartburn, nausea and vomiting.

ALKOXYLATED LONG CHAIN ALCOHOL

LD50 (Oral).> 2000 mg/kg rat

ALKOXYLATED FATTY ALCOHOL, POLYMER

LD50 (Oral).> 2000 mg/kg rat

2-PROPANOL

LD50 (Oral).4710 mg/kg Rat

LD50 (Skin).12800 mg/kg Rat

LC50 (Inhalation).72.6 mg/l/4h Rat

SECTION 12. Ecological information

Use this product according to good working practices; do not litter. Inform the competent authorities if the product reaches waterways or sewers or if it contaminates soil or vegetation.

12.1. Toxicity

ALKOXYLATED LONG
CHAIN ALCOHOL

**ASCOR AD**

LC50 - Fish. > 10 mg/l/96h fish

ALKOXYLATED FATTY
ALCOHOL, POLYMER
LC50 - Fish. > 10 mg/l/96h fish

2-PROPANOL
EC50 - Crustaceans. > 100 mg/l/48h Daphnia M.

12.2. Persistence and degradability

2-PROPANOL
Rapidly Biodegradable.

The preparation contains substances conforming to the biodegradability requirements of Reg. 648/04/EC.

12.3. Bioaccumulative potential

2-PROPANOL
Partition coefficient: n-
octanol/water. 0.05

12.4. Mobility in the soil

Information not available.

12.5. Results of PBT and vPvB assessment

According to the available data, the product does not contain PBT or vPvB substances in a percentage higher than 0.1%.

12.6. Other adverse effects

Information not available.

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, if possible. Product residues are considered special hazardous waste. The hazard level of the waste which partially contains this product must be assessed according to the legal provisions in force.

The product must be disposed of by an authorized waste management company, in compliance with the national and any local laws.

CONTAMINATED PACKAGING

Contaminated packaging must be sent for recycling or disposal in compliance with the national waste management laws.

SECTION 14. Transport information



ASCOR AD

14.1. UN number.

Not applicable.

14.2. UN shipping number.

Not applicable.

14.3. Transport hazard classes.

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for users.

Not applicable.

14.7. Bulk transport according to annex II of MARPOL 73/78 and the IBC code.

Information non applicable.

SECTION 15. Regulatory information

Composition (648/04/EC): less than 5%: anionic tensioactives; 15-30% nonionic tensioactives.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category. None.

Restrictions to the product or the substances contained therein according to Annex XVII Regulation (EC) 1907/2006.



Product.

Point. 3

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorization (Annex XIV REACH).

None.

Substances subject to export notification Reg. (EC) 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Health controls.

Workers exposed to this hazardous chemical agent must have their health monitored in accordance with the provisions of art. 41 of Italian Law (D.Lgs.) 81 of 9 April 2008 unless the worker's health and safety risk is deemed to be irrelevant, according to the provisions of art. 224 par. 2.

D.Lgs. 152/2006 and amendments.

Emissions:

TAB. D Class 4 04.30 %

TAB. D Class 5 00.70 %

WATER 78.98 %

15.2. Chemical safety assessment

No chemical safety assessment was drawn up for the mixture or the substances contained therein.

SECTION 16. Other information

Hazard statements (H) referred to in sections 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Eye Irrit. 2	Eye irritant, category 2
Skin Irrit. 2	Skin irritant, category 2
STOT SE 3	Specific toxicity for target organs - single exposure, category 3
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.

**ASCOR AD**

- H315** Causes skin irritation.
H336 May cause drowsiness or dizziness.

KEY:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Half maximal effective concentration in the tested population
- EC NUMBER: Identification number in ESIS (European Chemical Substances Information System)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals
- IATA DGR: Dangerous Goods Regulations of the International Air Transport Association
- IC50: Half maximal inhibitory concentration in the tested population
- IMDG: International Maritime Dangerous Goods Code
- IMO: International Maritime Organization
- INDEX NUMBER: Identification number in Annex VI of the CLP
- LC50: Lethal concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational exposure level
- PBT: Persistent Bioaccumulative and Toxic according to REACH
- PEC: Predicted environmental concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- TLV: Threshold Limit Value
- TLV CEILING: Absolute exposure limit that should not be exceeded at any time.
- TWA STEL: Spot exposure limit
- TWA: Time weighted average exposure
- VOC: Volatile organic compound
- vPvB: Very Persistent and very Bio-accumulative according to REACH
- WGK: Water hazard class (Germany).

GENERAL REFERENCES:

1. Regulation (EU) 1907/2006 of the European Parliament (REACH)
 2. Regulation (EU) 1272/2008 of the European Parliament (CLP)
 3. Regulation (EU) 790/2009 of the European Parliament (I Atp.) CLP
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 of the European Parliament (II Atp.) CLP
 6. Regulation (EU) 618/2012 of the European Parliament (III Atp.) CLP
 7. Regulation (EU) 487/2013 of the European Parliament (IV Atp.) CLP
 8. Regulation (EU) 944/2013 of the European Parliament (V Atp.) CLP
 9. Regulation (EU) 605/2014 of the European Parliament (VI Atp.) CLP
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA Agency website

User notes:

The information contained in this sheet is based on the knowledge available to the producer on the date of the last version. It is the user's responsibility to satisfy himself that the information is complete and suitable for his own particular use.

The document must not be interpreted as a guarantee of any specific properties of the product.


As the use of the product is not under the direct control of the producer, the user is responsible for ensuring compliance with all hygiene and safety laws and provisions in force. No liability shall be accepted for improper use.

Train staff appropriately in the use of chemical products.

Amendments compared to the previous version.

Modifications have been made to the following sections:

12.

	Murotti Angelo srl	Version no. 3
	ASCOR AD	Revision date 24/07/2015 Printed on 24/07/2015 Page no. 12/13

APPENDIX: EXPOSURE SCENARIOS- N.2

PHASE: TRANSFER OF PROFESSIONAL PRODUCT VIA A DEDICATED SYSTEM (BOTTLE/MACHINE)(ref. AISE GEIS. 8b. 1.a.v1)

Transfer of a product in a fully closed system. No exposure for the worker.

(e.g.: Venturi system or dosing pump)



OPERATING CONDITIONS

Maximum duration	40 minutes/day
Process conditions	Process performed at room temperature Local exhaust ventilation (LEV) is not required; generally efficient ventilation in the work place is sufficient

RISK MANAGEMENT MEASURES

Conditions and measures concerning personal protective equipment (PPE), health and hygiene evaluation	Personal protective equipment is not required.
---	--

GENERAL ADVICE

Do not eat, drink, smoke or use live flames	
Wash hands after use. Avoid contact with damaged skin Do not mix with other products	
Leakage instructions	Dilute with water and collect
Additional advice	Follow the instructions on the label, the technical sheet and the SDS in sect. 7.


ENVIRONMENTAL MEASURES: Prevent the non-diluted product from reaching surface water

PRODUCT COMPOSITION PROPERTIES

The classification of the concentrated product can be found on the label and in sect. 2 of the SDS
The product classification is based on the ingredient classification. The list of ingredients contributing to the product classification can be found in sect. 3 of the SDS.
The exposure evaluation is based on the key limit values of the ingredients indicated in sect. 8 of the SDS
The product may contain sensitizing components which may cause an allergic reaction in some people. Sect. 15 of the SDS lists these sensitizing components, where applicable to the product.

USE DESCRIPTORS

SU 22: Professional uses
PC 35: Washing and cleaning products (including solvent-based products)
PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
ERC 8a: Wide dispersive indoor use of processing aids in open systems

	Murotti Angelo srl	Version no. 3
	ASCOR AD	Revision date 24/07/2015 Printed on 24/07/2015 Page no. 13/13

APPENDIX: EXPOSURE SCENARIOS-N.3

PHASE: USING A PROFESSIONAL PRODUCT IN A CLOSED SYSTEM (ref AISE GEIS 1.1.a.V1)

Use of a product in a fully closed system. The worker is not exposed to the product or its vapors (e.g. CIP washing, washing machines)



OPERATING CONDITIONS

Maximum duration	480 minutes/day
Process conditions	Process performed at room temperature Local exhaust ventilation (LEV) is not required; generally efficient ventilation in the work place is sufficient

RISK MANAGEMENT MEASURES

Conditions and measures concerning personal protective equipment (PPE), health and hygiene evaluation	Personal protective equipment is not required.
---	--

GENERAL ADVICE

Do not eat, drink, smoke or use live flames	
Wash hands after use. Avoid contact with damaged skin Do not mix with other products	
Leakage instructions	Dilute with water and collect
Additional advice	Follow the instructions on the label, the technical sheet and the SDS in sect. 7.

ENVIRONMENTAL MEASURES: Prevent the non-diluted product from reaching surface water

PRODUCT COMPOSITION PROPERTIES

The classification of the concentrated product can be found on the label and in sect. 2 of the SDS
The product classification is based on the ingredient classification. The list of ingredients contributing to the product classification can be found in sect. 3 of the SDS.
The exposure evaluation is based on the key limit values of the ingredients indicated in sect. 8 of the SDS
The product may contain sensitizing components which may cause an allergic reaction in some people. Sect. 15 of the SDS lists these sensitizing components, where applicable to the product.

USE DESCRIPTORS

SU 22: Professional uses
PC 35: Washing and cleaning products (including solvent-based products)
PROC 1: Use in a closed circuit; exposure improbable
ERC 8a: Wide dispersive indoor use of processing aids in open systems