



STRIP OFF

Paint stripper in Aerosol

FEATURES:

Deep action	Removes all types of paint, coatings, fillers and remnants on surfaces, which are resistant to solvents without risk to health. Deep removal of paints (acrylic, vinyl, glycerol, antifouling), paints and coatings.
Safe for operators	Free of chlorinated solvents. No R40 hazard classification (see MSDS).
For various applications	Usable on vehicle bodies, grilles, doors and gates, on the floor and walls, on moulds in the plastic-making industry.

SPECIFICATIONS :

Physical-chemical properties	Value
Form	Aerosol
Colour	Colourless
Door	C
Specific gravity (20°C)	0,79 g/cm ³
Miscibility in water	Not soluble
VOC (%)	82,8
Gross volume (ml)	800
Net volume (ml)	600

PRECAUTIONS FOR USE:

It is essential to do a trial on polyethylene, polypropylene and polyester. Do not apply to PVC, polystyrene, organic glass and rubber. It is recommended to use protective gloves and goggles. For more info see MSDS.

ACTIVE INGREDIENTS:

- ✓ No chlorinated solvents
- ✓ Penetrating agents
- ✓ Emulsifiers
- ✓ Thickeners

USE:

Shake the aerosol can before use. Scrape the paint on the base before application of the aerosol spray to increase penetration. Spray the treated area from a distance of about 20 cm. Leave to act for 10 - 15 minutes (according to the thickness of the coat or cement or filling to be removed) until the agent dries (penetration of the active substance and evaporation of the solvents). Blisters indicate the efficiency of the agent. Use a scraper and remove the entire paint coat or remains. To remove coats, you may use a dry rag, scraper or metallic brush. Rinse with water.

All information in this document is based on our practical experience and/or laboratory tests. Due to the large spectrum of circumstances for usage and unpredictable human factors, we recommend that you always test our products before final usage. This technical data sheet has perhaps already been revised based on legislation, availability of the individual ingredients or newly acquired information. We can send you upon request the latest valid version, which is at the same time the sole valid version.

