TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Revision nr. 2

Dated 02/04/2020

Printed on 12/06/2020

Page n. 1/14

Replaced revision:1 (Dated: 17/03/2020)

Safety Data Sheet According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code:

SOLUZIONE IDROALCOLICA ETILICO 70% Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use Ethyl hydroalcoholic solution 70%. Uses advised against: Different uses than those intended.

1.3. Details of the supplier of the safety data sheet

DE VECCHI GIUSEPPE SRL Name

Indirizzo, VIA DON L. STURZO 7/9

Località e Stato. 20872 COLNAGO DI CORNATE D'ADDA (MB)

Telefono 039695142 Fax 0396095237

E-mail: info@devecchigiuseppesrl.com

e-mail address of the competent person responsible for the Safety Data Sheet Product distribution by:

1.4. Emergency telephone number

For urgent inquiries refer to

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2 H225 Highly flammable liquid and vapour. H319 Eye irritation, category 2 Causes serious eye irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Revision nr. 2

Dated 02/04/2020

Printed on 12/06/2020

Page n. 2/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

Hazard statements:

Signal words:

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

DANGER

Precautionary statements:

P501 Dispose of contents / container to in accordance with local and national regulations.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P101 If medical advice is needed, have product container or label at hand. P370+P378 In case of fire: use carbon dioxide, foam, chemical powder to extinguish.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

ETHANOL

CAS 64-17-5 Flam. Liq. 2 H225, Eye Irrit. 2 H319 $65 \le x < 70$

EC 200-578-6

INDEX 603-002-00-5

Reg. no. 01-2119457610-43

ETHYL METHYL KETONE

CAS 78-93-3 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066 $0 \le x \le 0,984$

EC 201-159-0 INDEX 606-002-00-3 Reg. no. 01-2119457290-43

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor: symptomatically treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Revision nr. 2 Dated 02/04/2020

Printed on 12/06/2020

Page n. 3/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures. Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 3

7.3. Specific end use(s)

Ethyl hydroalcoholic solution 70%.

ΕN

NOWAL CHIMICA S.R.L.

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Revision nr. 2 Dated 02/04/2020

Printed on 12/06/2020

Page n. 4/14

Replaced revision:1 (Dated: 17/03/2020)

SECTION 8. Exposure controls/personal protection

8.1. Control parameters
Regulatory References:

Regulatory R		
AUS	Österreich	Gesamte Rechtsvorschrift für Grenzwerteverordnung 2018, Fassung vom 17.10.2018
BEL	Belgique	AR du 11/3/2002. La liste est mise à jour pour 2017
BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
CHE	Suisse / Schweiz	Valeurs limites d`exposition aux postes de travail en Suisse: valeurs VME/VLE. Version Mars 2018 (SUVA)
CYP	Κύπρος	K.Δ.Π. 268/2001; K.Δ.Π. 55/2004; K.Δ.Π. 295/2007; K.Δ.Π. 70/2012; K.Δ.Π. 16/2019
CZE	Česká Republika	Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb.,
	·	kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Bekendtgørelse om ændring af bekendtgørelse om grænseværdier for stoffer og materialer1-
ESP	España	BEK nr 655 af 31/05/2018 LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019
ГОТ	F 4:	(INSST)
EST	Eesti	Töökeskkonna keemiliste ohutegurite piirnormid. Vastu võetud Vabariigi Valitsuse 18. septembri 2001. a määrusega nr 293 (RT I 2001, 77, 460), jõustunud 29.09.2001. Muudetud
		järgmise määrusega (kuupäev, number, avaldamine Riigi Teatajas, jõustumise aeg):
FINI	0	11.10.2007 nr 223 (RT I 2007, 55, 369) 1.01.2008
FIN	Suomi	HTP-VÄRDEN 2018. Koncentrationer som befunnits skadliga. SOCIAL- OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 10/2018
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
GRC	Ελλάδα	ΕΦΗΜΕΡΙΔΑ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 152 - 21 Αυγούστου 2018
HRV	Hrvatska	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 91/18)
HUN	Magyarország	A pénzügyminiszter 7/2018. (VIII. 29.) PM rendelete a munkahelyek kémiai biztonságáról szóló 25/2000. (IX. 30.) EüM- SZCSM együttes rendelet módosításáról
IRL	Éire	2018 Code of Practice for the Chemical Agents Regulations Safety Authority
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
LTU	Lietuva	LIETUVOS HIGIENOS NORMA HN 23:2011 "CHEMINIŲ MEDŽIAGŲ PROFESINIO POVEIKIO RIBINIAI DYDŽIAI. MATAVIMO IR POVEIKIO VERTINIMO BENDRIEJI
		REIKALAVIMAI. Nr. V-695/A1-272, 2018-06-12, paskelbta TAR 2018-06-15, i. k. 2018-09988
LUX	Luxembourg	Règlement grand-ducal du 20 juillet 2018 modifiant le règlement grand-ducal du 14 novembre
		2016 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à
		des agents chimiques sur le lieu de travail
LVA	Latvija	Ķīmisko vielu aroda ekspozīcijas robežvērtības (AER) darba vides gaisā 2018
NLD	Nederland	Regeling van de Staatssecretaris van Sociale Zaken en Werkgelegenheid van 13 juli 2018, 2018-0000118517 tot wijziging van de Arbeidsomstandighedenregeling in verband met de
NOD		implementatie van Richtlijn 2017/164 in Bijlage XIII
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005
POL	Polska	nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5 ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12
DDT	Dominional	czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de
		protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição
DOLL	D • ! -	a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTARARE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea
		protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
SVK	Slovensko	Nariadenie vlády č. 33/2018 Z. z. Nariadenie vlády Slovenskej republiky, ktorým sa mení a
		dopĺňa nariadenie vlády Slovenskej republiky č. 355/2006 Z. z. o ochrane zamestnancov pred
SVN	Slovenija	rizikami súvisiacimi s expozíciou chemickým faktorom pri práci v znení neskorších predpisov Uradni list Republike Slovenije 04.12.2018 - Uradnem listu RS št. 78 -PRAVILNIK o varovanju
	Sieverija	delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
SWE	Sverige	Hygieniska gränsvärden. AFS 2018:1
TUR	Türkiye	KİMYASAL MADDELERLE ÇALIŞMALARDA SAĞLIK VE GÜVENLİK ÖNLEMLERİ
1010	Talkiyo	HAKKINDA YÖNETMELİK - Resmi Gazete Tarihi: 12.08.2013 Resmi Gazete Sayısı: 28733
EU	OEL EU	Direttiva (UE) 2017/2398; Direttiva (UE) 2017/164; Direttiva 2009/161/UE; Direttiva
	TI \ / A C C !!!	2006/15/CE; Direttiva 2004/37/CE; Direttiva 2000/39/CE; Direttiva 91/322/CEE.
	TLV-ACGIH	ACGIH 2019

Revision nr. 2 Dated 02/04/2020

Printed on 12/06/2020

Page n. 5/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Threshold Limit Val			-111	ANOL			
Туре	Country	Country TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		•
MAK	AUS	1900	1000	3800	2000		STEL:60(Mow),Häufigke t/Sch:3x
VLEP	BEL	1907	1000				t/OCH.3X
TLV	BGR	1000	•	,	,	•	•
VME/VLE	CHE	960	500	1920	1000	•	
MAK	CHE	960	500	1920	1000	·	•
TLV	CZE	1000	532	3000	1596		
AGW	DEU	380	200	1520	800		
MAK	DEU	380	200	1520	800		
TLV	DNK	1900	1000				
VLA	ESP			1910	1000		
TLV	EST	1000	500	1900	1000	<u>. </u>	.
HTP	FIN	1900	1000	2500	1300	•	
VLEP	FRA	1900	1000	9500	5000		
WEL	GBR	1920	1000				
TLV	GRC	1900	1000				
GVI/KGVI	HRV	1900	1000	·		•	
OELV	IRL				1000		
RD	LTU	1000	500	1900	1000	.	
RV	LVA	1000	·	·		•	
TGG	NLD	260	·	1900		SKIN	
TLV	NOR	950	500	·		•	
NDS/NDSCh	POL	1900	<u> </u>	.	·	.	
TLV	ROU	1900	1000	9500	5000	•	
NPEL	SVK	960	500	1920	1000	.	
MV	SVN	960	500	1920	1000		
NGV/KGV	SWE	1000	500	1900 (C)	1000 (C)	.	
TLV-ACGIH	·		<u>.</u>	1884	1000	<u> </u>	·
Predicted no-effect cond	centration - PNEC	•		·		•	•
Normal value in fresh w	ater			0,96	m	g/l	.
Normal value in marine	water			0,79	m	g/l	·
Normal value for fresh v	vater sediment			3,6	m	g/kgdw	.
Normal value for marine	e water sediment			2,9	m	g/kgdw	.
Normal value for water,	intermittent release			2,75	m	g/l	
Normal value of STP mi	icroorganisms			580	m	g/l	
Normal value for the foo	od chain (secondary pois	oning)		0,72	m	g/kg	<u>.</u>
Normal value for the ter	restrial compartment			0,63	mg	g/kgdw	

ETHYL METHYL KETONE

Threshold Limit Value

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Revision nr. 2 Dated 02/04/2020

Printed on 12/06/2020

Page n. 6/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

Туре	Country		TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	Obscivations		
MAK	AUS	295	100	590	200	SKIN	.	
VLEP	BEL	600	200	900	300	·		
TLV	BGR	590		885				
VME/VLE	CHE	590	200	590	200	SKIN	.	
MAK	CHE	590	200	590	200	SKIN		
TLV	CYP	600	200	900	300	<u> </u>	·	
TLV	CZE	600	÷	900	•	<u> </u>	.	
AGW	DEU	600	200	600	200	SKIN		
MAK	DEU	600	200	600	200	SKIN	.	
TLV	DNK	145	50	.	•	SKIN	.	
VLA	ESP	600	200	900	300			
TLV	EST	600	200	900	300	·	·	
HTP	FIN	•		300	100	SKIN		
VLEP	FRA	600	200	900	300	SKIN		
WEL	GBR	600	200	899	300	SKIN	.	
TLV	GRC	600	200	900	300	·		
GVI/KGVI	HRV	600	200	900	300	SKIN	.	
AK	HUN	600	·	900		·	.	
OELV	IRL	600	200	900	300	SKIN	.	
VLEP	ITA	600	200	900	300	<u>.</u>		
RD	LTU	600	200	900	300			
VL	LUX	600	200	900	300			
RV	LVA	200	67	900	300			
TLV	NOR	220	75	·		<u>.</u>		
NDS/NDSCh	POL	450		900				
VLE	PRT	600	200	900	300	·	.	
TLV	ROU	600	200	900	300			
NPEL	SVK	600	200	900				
MV	SVN	600	200	900	300			
NGV/KGV	SWE	150	50	300	100			
ESD	TUR	600	200	900	300			
OEL	EU	600	200	900	300	<u>.</u>	.	
TLV-ACGIH	·	590	200	885	300	<u>.</u>	,	
Predicted no-effect cond	entration - PNEC					•		
Normal value in fresh water				55,8	n	ng/l		
Normal value for fresh w		284,74	n	ng/kg				
Normal value for marine water sediment				284,7	m	ng/kg		
Normal value for water, intermittent release				55,8	n	ng/l		
Normal value of STP microorganisms				709	n	ng/l		
Normal value for the food chain (secondary poisoning)				1000	- n	ng/kg	·	

Revision nr. 2

Dated 02/04/2020

Printed on 12/06/2020

Page n. 7/14

Replaced revision:1 (Dated: 17/03/2020)

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Normal value for the terrestrial compartment

22,5

mg/kg

Health - Derived no-eff	Effects on con:				Effects on wo	rkers		
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	31 mg/kg bw/d				
Inhalation			VND	106 mg/m3			VND	600 mg/m3
Skin			VND	412 mg/kg bw/d			VND	1161 mg/kg bw/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear opencircuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liauid

Colour pink / colorless Odour alcohol Odour threshold Not available

Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available < 23 °C Flash point **Evaporation Rate** Not available ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Revision nr. 2

Dated 02/04/2020

Printed on 12/06/2020

Page n. 8/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Not available Upper explosive limit Vapour pressure 30,74 mmHg Vapour density Not available

Relative density 0,87 - 0,89 Kg/I (20°C)

Solubility in water: total Partition coefficient: n-octanol/water Not available Auto-ignition temperature Not available Decomposition temperature Not available Not available Viscosity Not available Explosive properties Oxidising properties Not available

9.2. Other information

VOC (Directive 2010/75/EC): 69,90 % - 615,12 g/litre VOC (volatile carbon): 36,41 % - 320,42 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL METHYL KETONE

Reacts with: strong oxidising agents, light metals.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

Risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride, acids, concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver, silver nitrate, ammonia, silver oxide, ammonia, strong oxidising agents, nitrogen dioxide. May react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms explosive mixtures with: air.

ETHYL METHYL KETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHANOL

Avoid exposure to: sources of heat, naked flames.

ETHYL METHYL KETONE

Avoid exposure to: sources of heat.

10.5. Incompatible materials

ETHYL METHYL KETONE

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Revision nr. 2 Dated 02/04/2020

Jaleu 02/04/2020

Printed on 12/06/2020

Page n. 9/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANOL

In decomposition develops: gases and vapors potentially harmful to health.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available.

Information on likely routes of exposure

Information not available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available.

Interactive effects

Information not available.

ACUTE TOXICITY

 LC50 (Inhalation) of the mixture:
 Not classified (no significant component)

 LD50 (Oral) of the mixture:
 Not classified (no significant component)

 LD50 (Dermal) of the mixture:
 Not classified (no significant component)

ETHANOL

LD50 (Oral) > 5000 mg/kg Rat LC50 (Inhalation) 120 mg/l/4h

ETHYL METHYL KETONE

 LD50 (Oral)
 2737 mg/kg Rat

 LD50 (Dermal)
 6480 mg/kg Rabbit

 LC50 (Inhalation)
 23,5 mg/l/8h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY

Revision nr. 2

Dated 02/04/2020

Printed on 12/06/2020

Page n. 10/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

ETHANOL

LC50 - for Fish 13000 mg/l/96h Salmo gairdneri EC50 - for Crustacea 12340 mg/l/48h Daphnia magna 275 mg/l/72h Chlorella vulgaris EC50 - for Algae / Aquatic Plants

12.2. Persistence and degradability

ETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

ETHYL METHYL KETONE

Solubility in water > 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

ETHANOL

Partition coefficient: n-octanol/water -0,35

ETHYL METHYL KETONE

Partition coefficient: n-octanol/water 0,3

12.4. Mobility in soil

Information not available.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

Revision nr. 2 Dated 02/04/2020

Printed on 12/06/2020

Page n. 11/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA:

14.2. UN proper shipping name

ADR / RID: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) IMDG: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) IATA: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33 Limited Quantities: 1 L Tunnel restriction code: (D/E)

Special Provision: -

IMDG: EMS: F-E, S-D Limited Quantities: 1 L

IATA: Maximum quantity: 60 L Cargo: Packaging instructions: 364 Pass.: Maximum quantity: 5 L Packaging instructions: 353

> A3, A58, A180 Special Instructions:

Revision nr. 2

Dated 02/04/2020

Printed on 12/06/2020

Page n. 12/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None.

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the mixture.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2

Eye Irrit. 2 Eye irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)

Revision nr. 2 Dated 02/04/2020

Printed on 12/06/2020

Page n. 13/14

Replaced revision:1 (Dated: 17/03/2020)

ΕN

TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%

- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

Classification and procedure used to derive it in accordance with Regulation (EC) 1272/2008 (CLP) in relation to mixtures:

Classification according to Regulation (EC) No. 1272/2008	Classification procedure
Flam. Liq. 2 H225	Based on experimental data
Eye Irrit. 2 H319	Calculation method

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- FCHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

NOWAL CHIMICA S.R.L.	Revision nr. 2 E
TVA1334 - SOLUZIONE IDROALCOLICA ETILICO 70%	Printed on 12/06/2020
TVA 1334 - SOLUZIONE IDROALCOLICA ETILICO 70%	Page n. 14/14
	Replaced revision:1 (Dated: 17/03/2020)
hanges to previous review: he following sections were modified: 2 / 03 / 08 / 09 / 14 / 15.	
ne following sections were modified: 2 / 03 / 08 / 09 / 14 / 15.	